
Cavendish Seat



1800 Cavendish Seat with flush mounted plaque



1500 Cavendish Seat finished in dark Oak stain



A heavyweight seat having substantial timber sections that give increased strength, whilst retaining the inherent elegance of this traditional design. This model is principally intended for parks and other municipal uses.

- Available in Iroko planed and sanded as standard or stained at additional cost, or seasoned European Oak
- Seat base slats 25 x 65mm finished
- Legs 70 x 70mm finished
- Back and front rails 45 x 95mm finished
- Back slats 16 x 50mm finished
- Mid rails 40 x 70mm finished
- Length 1500mm, weight approx. 36kg
- Length 1800mm, weight approx. 40kg
- Length 2400mm, weight approx. 49kg
- (Central leg and arm version 62kg)
- Supplied fully assembled
- See our website for fixing options

The particularly deep main rails shorten the length of the back slats which are a generous 16mm thick. This reduces the risk of the back slats being kicked out by vandals, which can be a problem with all seats of this type.

The stainless steel screws used in the construction of this seat are fully plugged, and the main tenon joints are double-dowelled.

2400 Cavendish seats can be specified in standard form (with two frames) with an additional central leg, or an additional leg and arm.

The 2400 version with the central leg only is particularly traditional in appearance. As well as providing significantly increased strength, the 2400 central leg and arm version has an extra arm for the elderly and disabled, and discourages vagrants from sleeping on the seat.

Central frames also enable longer versions to be manufactured. 3600mm is the largest practical size, because of transportation difficulties.

Commemorative versions with special back panels are normally produced for important national events (see page 4).

See our website for images of seats larger than 1800mm.



1800 Cavendish Seat in Iroko



1800 Cavendish Seat in Iroko (stained)



1800 Cavendish Seat in Iroko with back panel